

Our hybrid range of stretch wrapping films are the latest technology in load containment.

## Hybrid Hand Film

---

Designed to minimise the stress on the operator, whilst applying the stretch film, hybrid is the leader in the market.

Applied by forward motion and not by walking backwards and dragging the film, hybrid should be the only choice in hand wrapping technology.

## Hybrid Machine Film

---

Designed specifically to achieve better film yield in "Force to load" pallet wrapping machinery, Hybrid films give similar performance and load containment to stretch films normally purchased for the most high tech wrapping applications.

Hybrid machine films can lower the cost per pallet wrapped by more than 40% compared to traditional films on the same machines.



### ★ Features

---

- High gloss lamination
  - Instant stretch
  - Transparent
  - Easy to apply
  - Hand film available in black for load security
- 

### + Benefits

---

- Low cost per pallet
  - OH&S advantages for users
  - Lightweight yet strong
  - High puncture resistance
  - Great load containment
-

Every metre matters is a new initiative by FROMM to highlight the discrepancies in the market and educate customers on what is right.



At FROMM Packaging we are always working hard to ensure we provide high quality products to our customers. We guarantee that every roll of FROMM and pallet wrapping film that you purchase is the same length as quoted in the FROMM Technical Data Sheet at a minimum. So if it's a 2000 metre roll, you will get 2000 metres, guaranteed.

Some stretch film resellers have up to 5% variation batch to batch. This could mean the difference of 100 metres on every roll.

FROMM provide a technical data sheet for every style of film. The data sheet outlines all the technical specifications and states the amount of film on every roll

**Technical Data Sheet**

Product Code	Hybrid120.M		
Product	Pallet wrapping film		
Grade	500mm x 2500m x 12um		
Colour	Clear		
Date	01/02/2019		
Issue Number	FPA001		

Physical Properties	Units	Standard	Specification	Testing Method
Thickness	Microns	12±1	15	Thickness Gauge
Width	mm	500±1	500	Ruler
Length	Metres		2500	Meter Setting

Mechanical Properties	Units	Reading	Testing Method
Tensile Strength	MD	29	ASTM D 0882
	TD	14	
Elongation	MD	178	
	TD	413	
Impact Strength	gm	58	ASTM D 1709
Haze	%	1.7	ASTM D 1003

FROMM Packaging Australia guarantee that every roll of FROMM stretch wrapping film that you purchase is the same length as quoted in the FROMM Technical Data Sheet at a minimum.

Australia Wide  
PO Box 4018, Mount Ommanney QLD 4074, Australia  
Tel: 1800 023 890 | info@fromm-pack.com.au  
www.fromm-pack.com.au | ABN 42 070 702 887

## ★ Technical Specifications

Product Code	Film Dimensions	Thickness	Film Type
Hybrid.S	500mm x 400m	12um	Clear - Hand Film
Hybrid.SHD	500mm x 300m	15um	Clear - Hand Film
Hybrid.BLK	500mm x 300m	15um	Black - Hand Film
Hybrid120.M	500mm x 2500m	12um	Clear - Machine Film

**FROMM** | PACKAGING AUSTRALIA

Australia Wide

T 1800 023 890

E info@fromm-pack.com.au

W www.fromm-pack.com.au